

1.0 RESPONSIBLE PARTY

- 1.1 Any and all questions or correspondence regarding this document and specifications herein shall be directed to:

Code Blue Corporation
92 East 64th Street
Holland, MI 49423
616-392-8296
aespecs@codeblue.com

2.0 SCOPE

- 2.1 This document is intended to provide complete and accurate specifications of the CB1e product offering by Code Blue Corporation for the purpose of inclusion in project specifications, requirements and recommendations required by potential users of Code Blue products and services.
- 2.2 The CB1e will be referred to as “unit” throughout this document.
- 2.3 Code Blue Corporation will be referred to as “manufacturer” throughout this document.

3.0 PRODUCT DESCRIPTION

- 3.1 The unit shall be an easily identifiable, vandal resistant communications device that is Americans with Disabilities Act (ADA) compliant, multi-functional, freestanding, and constructed of heavy steel. The unit shall be aesthetically pleasing and virtually impervious to damage, and shall include a high quality, vandal resistant, hands-free communications device illuminated by a high intensity faceplate light, a powerful strobe light, and a vivid blue beacon that serves to identify the unit from a great distance.

4.0 CONSTRUCTION

- 4.1 The unit shall be a cylinder constructed of ASTM A500 seamless carbon steel structural tube, schedule 20, 12.75” OD x 0.25” thick wall and a height of not less than 9 feet.
- 4.2 Tamper resistant proprietary fasteners manufactured for Code Blue Corporation shall be used. It shall not be possible to acquire the custom designed bit from any source other than Code Blue Corporation. It shall not be possible to enter nor remove any component without this bit. All other types of fasteners shall not be acceptable under any circumstance.
- 4.3 The unit shall have an internal anchor base plate that is MIG welded to the unit 2” above its base. The base plate shall be fabricated with a minimum of .50” thick A-36 grade steel plate and shall have a 5” diameter center hole for electrical conduit access. The base



Architectural & Engineering Specifications

- plate shall have four (4) oblong holes on an 8" circular bolt pattern for the attachment to anchor bolts.
- 4.4 The unit shall have an access opening near the base of the unit which provides access for mounting to the anchor bolts and connectivity to electrical facilities. The access opening shall have a cover plate which mounts flush with the unit. This cover plate shall be the same steel and radius as the unit. The cover plate shall fit precisely into the opening and have a weather resistant gasket to prevent water and other elements from entering the unit. The cover plate shall be held in place by two (2) ¼" x 20 x 1" counter sunk proprietary fasteners supplied only by manufacturer.
- 4.5 The unit shall have a dome top assembly which seals the top of the unit and shall consist of a mounting ring, gasket, LED beacon/strobe, UV rated polycarbonate dome and required fasteners.
- 4.5.1 The mounting ring shall be made of high quality cast aluminum and be free from defects. The diameter shall be equal to the unit and three tabs; each with a 10-24 x 1" stainless steel thumbscrew for fastening to the unit. The mounting ring shall have a weather resistant gasket mounted to the bottom to prevent water and other elements from entering the unit. The mounting ring shall have a brush gasket mounted between the exterior of the ring and the UV rated polycarbonate dome to allow passive air flow through the unit and prevent insects and other environmental particles from entering the unit.
- 4.5.2 A cylindrical, transparent, UV rated polycarbonate dome that is a minimum of six 6" tall with a 12.5" outer diameter shall be attached to the mounting ring with three (3) proprietary fasteners. The dome shall be made of a clear UV rated polycarbonate and shall be sloped to prevent pooling of water.
- 4.5.3 A Blue LED Beacon/Strobe shall be attached to the mounting ring with three (3) Phillips head screws below the dome.
- 4.6 A recessed opening shall be cut into the unit at a point beginning 36.6" above the bottom of the unit. The opening shall be 15.1" tall at the forward edge and 12.8" tall at the rear edge creating a 25 degree angle from the horizontal. The upper horizontal edge of the opening shall constitute an arc of 160 degrees in the face of the unit and the sides of the opening shall be parallel and the same length.
- 4.6.1 The opening shall be totally enclosed by a 7 gauge steel plate that shall have a single opening allowing for a communication device. The plate shall be seam welded to the unit so that the plate and the unit appear to be one unit.

5.0 MOUNTING

- 5.1 The unit shall be mounted onto four anchor bolts that are set into concrete. Standard ¾" x 24" galvanized steel anchor bolts, nuts and washers shall be used as supplied. The unit shall mount ½" above the concrete to allow air flow within the unit.

Code Blue® • 92 East 64th ST • Holland, MI 49423 • 800.205.7186 • www.codeblue.com

Specifications are subject to change without prior notice. Latest information available at www.codeblue.com.
Code Blue is a registered trademark of Code Blue Corporation.



6.0 ELECTRICAL

- 6.1 All electrical components shall have a modular plug for easy service and replacement. All electrical wiring shall be concealed within the unit and shall not be visible from the outside of the unit.
- 6.2 All electrical components in the unit shall be equipped with a fuse for protection from transient voltage conditions.
- 6.3 The unit shall require 1 ampere at 24v AC standard.
- 6.4 The unit shall have the option for Power over Ethernet for connectivity to a VoIP network switch with 802.3af (minimum) capabilities. Requires the IP5000 phone for connectivity to ToolVox Communication Manager or SIP/IAX2 compatible VoIP system. Refer to the Power over Ethernet Architect and Engineering Specification.
- 6.5 The unit shall have the option of a Power Brick for connectivity to 120v AC, 240v AC, 277v AC and 347v AC primary power. Refer to the Power Brick Architect and Engineering Specification.
- 6.6 The unit shall have the option for a NightCharge system. Refer to the NightCharge Architect and Engineering Specification.
- 6.7 The installer shall follow all NEC and local electrical codes when installing the unit power systems.

7.0 LIGHTS

- 7.1 LED Beacon/Strobe: An LED Beacon/Strobe shall be located in the dome top assembly and have a Lumen rating of no less than 14.5. The LED Beacon/Strobe shall have a factory set flash rate of no less than 60 flashes per minute and be programmable. A deep blue UV rated polycarbonate prismatic refractor shall surround the LED Beacon/Strobe and shall be used to distribute the light in a horizontal pattern for maximum brightness and visibility at a distance.
 - 7.1.1 The communication device shall be factory programmed to activate the LED Beacon/Strobe for the duration of a button 1 (“Red Button”, “Emergency” or “Push for Help”) call. The LED Beacon/Strobe cannot be deactivated at the unit.
- 7.2 Faceplate Light: A LED Faceplate Light shall be mounted within the unit above the recessed opening which houses the communications device. This fixture will direct light onto the communications device and shall be vandal resistant.

8.0 COMMUNICATIONS

- 8.1 The unit shall have a high quality vandal resistant and ADA compliant speakerphone communication device.



Architectural & Engineering Specifications

- 8.1.1 IP5000 - VoIP: Refer to the IP5000 Architect and Engineering Specification for further information.
- 8.1.2 IA4100 - Analog: Refer to the IA4100 Architect and Engineering Specification for further information.
- 8.2 The unit shall be capable of communicating through an integrated 802.11g, 2.4 GHz IP wireless system. Refer to the IP Wireless Architect and Engineering Specifications.
- 8.3 The unit shall be capable of communicating through an integrated Secure Mesh wireless system operating at 2.4 – 5.9 GHz. Refer to the Secure Mesh Wireless Architect and Engineering Specifications.
- 8.4 The unit shall be capable of communicating through an integrated GSM Cellular device. Refer to the GSM Cellular Architect and Engineering Specifications.
- 8.5 EIA/TIA, ANSI, CSA and BICSI cabling or similar standards shall be adhered to for proper operation of Code Blue communication devices connected to copper or fiber infrastructure.

9.0 FINISH

- 9.1 The unit shall be finished with a highly graffiti and UV resistant coating process.
- 9.2 Substrate preparation shall be as required to comply with applicable ASTM impact and adhesion standards:
 - D2794 Direct and Reverse Impact
 - D523 Gloss @ 60 Degrees
 - D3359B Cross hatch Adhesion
 - D1654 Corrosion Creep
 - D714 Scribe Blisters
 - D714 Field Blisters
- 9.3 The polyurethane finish shall be a multi coat system available in 10 standard colors:
 - Safety Blue
 - Safety Red
 - Safety Yellow
 - Midnight Blue
 - Gloss White
 - Gloss Black
 - Medium Bronze
 - Dark Bronze
 - British Racing Green
 - Cardinal Red



Architectural & Engineering Specifications

- 9.4 Custom colors shall be available as specified by the user and approved by the manufacturer.
- 9.5 The primer coat and finish coat shall each have a minimum coverage thickness of 2.0 mils.
- 9.6 No other types of finishes are acceptable.

10.0 GRAPHICS

- 10.1 The graphics shall be a durable Nikkalite engineering grade reflective vinyl for high visibility and legibility.
- 10.2 Standard 30" length graphics text offering shall be:
 - EMERGENCY
 - ASSISTANCE
 - SECURITY
 - COURTESY
 - POLICE
- 10.3 Standard graphics color offering shall be:
 - Reflective White
 - Reflective Blue
 - Reflective Black
 - Reflective Green
 - Reflective Red
 - Reflective Yellow
- 10.4 Custom graphics text, length and color shall be available by the manufacturer.

11.0 GENERAL OPTIONS

- 11.1 The following optional equipment shall be available for the unit by the manufacturer. Please refer to the associated Architect and Engineering Specification:
 - Active Vent Solar Powered Fan
 - Overhead Camera Mount
 - PAS 1/5 Mass Notification System

12.0 WARRANTY

- 12.1 The unit shall be warranted for a period of two (2) years. Reference manufacturer's warranty for further details.

13.0 MANUFACTURER

- 13.1 The manufacturer shall be Code Blue Corporation of Holland, Michigan. There are no known equivalents.
- 13.2 Code Blue Corporation manufactures its products according to the most recent revision of our product specifications and shall not be held responsible for obsolete or outdated specifications. For the latest revision please refer to www.codeblue.com or contact Code Blue Corporation directly.