


DEALER INFORMATION

Dealer:	City:	State:	PO:	Date:
End User (required for valid order):	City:	State:	Type:	

STANDARD FEATURES

Basic Unit Configuration



- Code Blue Flush Mounted Enclosure (CB FME) faceplate wall mount

Standard Finish Color

- As Supplied

Graphics Color

- None

Graphics Text

- None

OPTIONAL FEATURES

Speakerphone Options

- IA4100 FP1 analog speakerphone with single red button "Push For Help" (standard)
- IA4100 FP2 analog speakerphone with 2nd button (additional black "Info" button)
- IA4100 FP2-K analog speakerphone with 2nd button (additional black "Call" button) and keypad
- IP5000 FP1 analog speakerphone with single red button "Push For Help"
- IP5000 FP2 analog speakerphone with 2nd button (additional black "Info" button)
- IP5000 FP2-K analog speakerphone with 2nd button (additional black "Call" button) and keypad

Main Bezel Options ("Push For Help" is standard)

- EMERGENCY (raised letters w/ Braille)
- EMERGENCY/EMERGENCIA (raised letters w/ Braille)

NOTE: A backup battery assembly is *required* when an IP speakerphone is connected to a non-PoE network switch with UPS backup. Reference *COMMUNICATIONS: IP5000 PHONE COMPONENTS* order form for purchase.

NOTE: Unit requires 24v AC or 12v DC power.

QUANTITY & TOTAL

Unit Price:	X	Quantity:	=	Total Price: (U.S. Dollars – excludes S&H)
-------------	----------	-----------	----------	---